




# Amlogic T972 4K

|            |                      |
|------------|----------------------|
| Processor  | Amlogic T972         |
| GPU        | ARM Mail-450         |
| RAM        | 2 GB                 |
| Storage    | 4 GB (32 GB) / 16 GB |
| Resolution | 4K@60                |
| Audio      | 2.4 BT4.2            |

|              |                           |
|--------------|---------------------------|
| Display      | 1 LVDS LCD 50/60 4K*2K@60 |
| Lighting     | 12 PWM Dimmer             |
| USB          | 1 * USB 2.0 * 1 * 3 USB   |
| Serial       | 4 UART (232/485) TTL      |
| Camera       | 1 * 2.1 MP 4K*2K@60       |
| Audio        | 4 Channels PDM            |
| Network      | 1 * 4G LTE                |
| IO           | TP/I2C/SPI/ADC            |
| Connectivity | IO RJ45 10/100            |
| RTC          | RTC                       |
| USB          | USB OTA                   |
| Storage      | 125 * 80                  |







PCB : 4-layer board  
 Size : 165mm\*95mm, Thickness 1.2mm  
 Screw hole specifications :  $\Phi 3.0\text{mm} \times 4$

Amlogic T792 Android  
 :  
 O2O

Amlogic T972 Cortex-A55 1.9 GPU Mali-G314

### 1.3

- ◆

